

Fastest Delivery on NYC Local Law 5 Certified E-Z Strip Cable

From Local Inventory at our New York Metro Warehouse

Lake Cable, LLC offers you New York City Certified LL5 Fire Alarm Cable that will simplify your fire installations, speed up your terminations and improve the bottom line on all your Local Law 5 projects. Lake Cable's exclusive E-Z STRIP jacket was developed with the installer in mind to enable quicker, more efficient cable installs for both 150°C and 200°C requirements.

When your fire alarm installation calls for New York City Certified Local Law 5 Cable, and delivery matters, simply contact Lake Cable. 150°C and 200°C shielded or non-shielded constructions are in stock and immediately available from Lake Cable's New York warehouse.

E-Z STRIP FEATURES:

- *Fast and Easy Stripping*
- *Meets NYC Local Laws*
- *Chemical Resistant Jacket*
- *Abrasion Resistant Material*
- *Easy to Install*

E-Z STRIP COMPLIANCES:

- *E-Z Strip Local Law 5*
- *150°C or 200°C from Lake Cable*
- *E-Z Strip 150°C or 200°C NYC Fire Alarm Cable*
- *150°C or 200°C Listed and Classified by U.L. for NYC*

LAKE CABLE
Exclusive



LAKE CABLE, LLC
WHEN DELIVERY MATTERS...



Lake E-Z Strip Local Law 5 Flame Safe 150°C or 200°C Unshielded or Shielded Plenum

APPLICATIONS: For use in indoor non-conduit, air plenum installations, floor warden and fire control stations, supervisory and associated systems, computer and microprocessor based fire alarm systems, fire alarms, signaling, smoke detection, fire alarm control circuits, heat detection devices, emergency evacuation systems, sprinkler waterflow alarms, locked door rails and voice communications.

LAKE E-Z STRIP UNSHIELDED PLENUM DESCRIPTION: 12 to 18 AWG solid bare copper conductors, Red FLAME SAFE 150°C or 200°C plenum rated insulation and jacket.

APPROVALS: UL Subject 1424 FPLP/NPLFP 150°C or 200°C Classified for NYC Cert. Fire Alarm Cable.

| PART NO. 150°C | CAP. | PART NO. 200°C | CAP. | COND. SIZE | NO. OF PAIRS | CABLE O.D. | WT. 1000' |
|-------------------|------|-------------------|------|---------------|-----------------|---------------|-----------|
| L121PR | 65 | FF122LL5 | 19 | 12 AWG | 1 | 0.272 | 62 |
| L122PR | 65 | FF122PRLL5 | 19 | 12 AWG | 2 | 0.413 | 91 |
| L141PR | 60 | FF142LL5 | 17 | 14 AWG | 1 | 0.238 | 44 |
| L142PR | 60 | FF142PRLL5 | 17 | 14 AWG | 2 | 0.359 | 83 |
| L143PR | 60 | FF143PRLL5 | 17 | 14 AWG | 3 | 0.383 | 116 |
| L161PR | 55 | FF162LL5 | 15 | 16 AWG | 1 | 0.212 | 32 |
| L162PR | 55 | FF162PRLL5 | 15 | 16 AWG | 2 | 0.315 | 60 |
| L163PR | 55 | FF163PRLL5 | 15 | 16 AWG | 3 | 0.336 | 82 |
| L181PR | 50 | FF182LL5 | 13 | 18 AWG | 1 | 0.190 | 24 |
| L182PR | 50 | FF182PRLL5 | 13 | 18 AWG | 2 | 0.281 | 44 |
| L183PR | 50 | FF183PRLL5 | 13 | 18 AWG | 3 | 0.299 | 60 |



LAKE CABLE
Exclusive



GAUGE: 12-18 AWG
TEMPERATURE: 150°C or 200°C
CONSTRUCTION: Cabled
GROUP ID: Each Pair Color Coded
CONDUCTOR: Solid Bare Copper
INSULATION: Flame Safe Plenum
JACKET: Flexible Plenum
COLOR CODE: Red (02)
LEGEND: PR AWG (UL) FPLP 150°C or 200°C Also Classified NYC Cert. Fire Alarm Cable
PACKAGING: Spools


LAKE E-Z STRIP SHIELDED PLENUM DESCRIPTION: 12 to 18 AWG solid bare copper conductors, Red FLAME SAFE 150°C or 200°C overall foil shield, tinned copper drain wire, plenum rated insulation, and jacket.

APPROVALS: UL Subject 1424 FPLP/NPLFP 150°C or 200°C Classified for NYC Cert. Fire Alarm Cable.

| PART NO. 150°C | CAP. | PART NO. 200°C | CAP. | COND. SIZE | NO. OF PAIRS | CABLE O.D. | WT. 1000' |
|-------------------|------|-------------------|------|---------------|-----------------|---------------|-----------|
| L121PRS | 127 | FF122LL5S | 36 | 12 AWG | 1 | 0.276 | 71 |
| L122PRS | 95 | FF122PRLL5S | 26 | 12 AWG | 2 | 0.417 | 129 |
| L141PRS | 112 | FF142LL5S | 32 | 14 AWG | 1 | 0.242 | 50 |
| L142PRS | 85 | FF142PRLL5S | 24 | 14 AWG | 2 | 0.362 | 90 |
| L143PRS | 75 | FF143PRLL5S | 21 | 14 AWG | 3 | 0.387 | 121 |
| L161PRS | 105 | FF162LL5S | 28 | 16 AWG | 1 | 0.216 | 36 |
| L162PRS | 75 | FF162PRLL5S | 21 | 16 AWG | 2 | 0.319 | 64 |
| L163PRS | 65 | FF163PRLL5S | 19 | 16 AWG | 3 | 0.340 | 86 |
| L181PRS | 90 | FF182LL5S | 25 | 18 AWG | 1 | 0.194 | 27 |
| L182PRS | 65 | FF182PRLL5S | 20 | 18 AWG | 2 | 0.284 | 47 |
| L183PRS | 60 | FF183PRLL5S | 18 | 18 AWG | 3 | 0.303 | 63 |



LAKE CABLE
Exclusive



GAUGE: 12-18 AWG
TEMPERATURE: 150°C or 200°C
CONSTRUCTION: Cabled
GROUP ID: Each Pair Color Coded
CONDUCTOR: Solid Bare Copper
INSULATION: Flame Safe Plenum
JACKET: Flexible Plenum
SHIELD: Aluminum Polyester Foil
COLOR CODE: Red (02)
LEGEND: PR AWG (UL) FPLP 150°C or 200°C Also Classified NYC Cert. Fire Alarm Cable
PACKAGING: Spools

THESE CABLES CAN BE MANUFACTURED IN MULTICONDUCTOR NON-PAIRED CONSTRUCTIONS.

